

**GPT HOOK-UP:** round construction wire is made of one, stranded conductor insulated with polyvinyl chloride. Wire used for connecting low voltage power in vehicles, control equipment, RVs and other. 300V, -20°C+60°C



**AUTOMOTIVE**

| Part Number | Gauge /strands | Colors  | Nominal Overall Diameter | Lengths (ft)         |
|-------------|----------------|---|--------------------------|----------------------|
| 1550        | 16/19          | Black, Blue, Brown, Green, Grey, Orange, Purple, Red, White, Yellow | 0.109"                   | 100ft, 500ft, 1000ft |
| 1560        | 14/41          | Black, Blue, Brown, Green, Grey, Orange, Purple, Red, White, Yellow | 0.125"                   | 100ft, 500ft, 1000ft |
| 1570        | 12/65          | Black, Blue, Brown, Green, Grey, Orange, Purple, Red, White, Yellow | 0.143"                   | 100ft, 500ft, 1000ft |
| 1580        | 10/105         | Black, Red, White, Yellow   | 0.188"                   | 50ft , 100ft, 500ft  |
| 1590        | 08/65          | Black, Red  | 0.217"                   | 50ft , 100ft         |
| 1600        | 06/65          | Black, Red  | 0.195"                   | 50ft, 100ft          |

**POWER FORCE:** round construction wire made of one, rope lay, stranded conductor insulated with flexible polyvinyl chloride. Wire used for connecting low-medium voltage power. 300V, -20°C+60°C



| Part Number | Gauge/strands | Colors     | Nominal Overall Diameter | Lengths (ft)                    |
|-------------|---------------|------------|--------------------------|---------------------------------|
| 1660        | 10/413        | Black, Red | 0.195"                   | 50ft, 100ft, 250ft 500ft        |
| 1662        | 08/665        | Black, Red | 0.248"                   | 50ft, 100ft, 250ft, 500ft       |
| 1666        | 04/1050       | Black, Red | 0.367"                   | 25ft, 50ft, 100ft, 250ft, 500ft |



**AUTOMOTIVE ZIPCORD:** duplex construction cable made of two, stranded conductors insulated with polyvinyl chloride (PVC) red and black color for polarity. Wire used to connect low voltage power in vehicles or other equipment.  
**300V, -20°C+60°C**



**AUTOMOTIVE**

| Part Number | Gauge/ strands | Nominal Overall Diameter | Lengths (ft)                      |
|-------------|----------------|--------------------------|-----------------------------------|
| 2440        | 18/16          | 0.100" x 0.215"          | 50ft, 100ft, 250ft, 500ft, 1000ft |
| 2445        | 16/26          | 0.110" x 0.235"          | 50ft, 100ft, 250ft, 500ft, 1000ft |
| 2450        | 14/41          | 0.120" x 0.255"          | 50ft, 100ft, 250ft, 500ft         |
| 2455        | 12/65          | 0.156" x 0.255"          | 50ft, 100ft, 250ft, 500ft         |
| 2460        | 10/105         | 0.195" x 0.405"          | 50ft, 100ft, 250ft                |
| 2465        | 8/65           | 0.230" x 0.470"          | 50ft, 100ft, 250ft                |



Registration, Evaluation and Authorisation of Chemicals

