



# SEMINOLE WIRE & CABLE

836 Camden Ave  
 Blenheim, NJ 08012  
 ph: 800-346-4378  
 fax: 856-228-0697  
[sales@seminolewire.com](mailto:sales@seminolewire.com)  
[www.seminolewire.com](http://www.seminolewire.com)

## Product Data Sheet - Pet Containment Wire

**Insulation:** Linear Low Density Polyethylene

**Application:** Direct Burial Pet Containment Wire

Part No.	AWG	Conductor Type	Conductor Stranding	Insulation Thickness	Nominal OD	Weight lbs. per 1,000 ft	Packaging*
DW20SOL	20	Bare Copper	Solid	0.028	0.088	5.22	F, D
DW18SOL	18	Bare Copper	Solid	0.038	0.116	8.44	B, E
DW18S	18	Bare Copper	16 / 30	0.038	0.123	8.53	B, E
DW16SOL	16	Bare Copper	Solid	0.045	0.140	13.25	B, C
DW16SOL6	16	Bare Copper	Solid	0.052	0.154	14.85	A, C
DW16CCS	16	Copper Clad Steel	Solid	0.045	0.140	12.25	B, C
DW16S	16	Bare Copper	19 / .0117	0.045	0.148	13.75	B, C
DW14SOL	14	Bare Copper	Solid	0.045	0.154	19	A, C
DW14S30	14	Bare Copper	19 / .0145	0.030	0.134	16	A, C
DW14S	14	Bare Copper	19 / .0145	0.045	0.164	19	A, C

### TWISTED

DW14TW	14	Bare Copper	19 / .0145	0.028	0.128	35.75	G
DW16TW	16	Bare Copper	Solid	0.028	0.106	21.30	C
DW16CTW	16	Copper Clad Steel	Solid	0.028	0.106	19.75	C
DW18TW	18	Bare Copper	16 / 30	0.028	0.103	15	C

\*Packaging/ spools per ctn.    A= 1 - 1,000 ft.    B= 2 - 1,000 ft.    C= 2 - 500 ft.    D= 4 - 1,000 ft.    E= 4 - 500 ft.    F= 8 - 500 ft.    G= 1 - 500 ft.

Custom spool length and color available upon request.