

COAXIAL: constructed of one conductor insulated with polypropylene, shielded and jacketed in polyvinyl chloride or polypropylene. Lengths from 50ft to 1000ft per reel or easy pay-out carton. Direct burial cable is marked with *.



VIDEO



Registration, Evaluation and Authorisation of Chemicals



Part Number	Type/ UL	Gauge/ strands	Dielectric Type (diameter)	Shield/ Coverage	Jacket (diameter)	IMP. (Ohm)	CAP. (pF/ft)	VDP	ATT. 100MHz-dB/100ft
3210	RG-59/U Non-UL (jan-c-17)	22 CCS	PE (0.146")	BC Braid 95%	Black PVC (0.240")	73	21	66%	3.3
3302	RG-59/U CM	20 BC	FPE (0.146")	BC Braid 95%	Black PVC (0.240")	80	16.3	78%	2.9
3552	RG-6/U CL2/CATV	18 CCS	FPE (0.180")	AL Foil 100% AL Braid 60%	Black PVC (0.270")	75	17.3	78%	2.1
3556*	RG-6/U Non-UL	18 CCS	FPE (0.180")	AL Foil 100% AL Braid 60%	Black PE (0.270")	75	17.3	78%	2.1
3602	RG-6/U CL2/CATV	18 CCS	FPE (0.180")	AL Foil 100% AL Braid 46% AL Foil 100% AL Braid 43%	Black PVC (0.275")	75	17.3	78%	2.1
3640	RG-11/U CL2/CATV	14 BC	FPE (0.285")	BC Braid 97%	Black PVC (0.405")	75	17.3	78%	1.6
4022	RG-59/U CM Siamese	20 BC 18/7 BC 18/7 BC	FPE (0.146") SR PVC (0.010" wall)	BC Braid 95% Unshielded	Black PVC (0.240" x 0.460")	75	17.3	78%	2.9

Acronyms:

AL - Aluminum

ATT - Attenuation

BC - Bare Copper

B Foil - Bonded Foil

CAP - Capacitance

CCA - Copper Clad Aluminum

CCS - Copper Clad Steel

FPE - Foam Polyethylene

IMP - Impedance

O.D. - Overall Diameter

NM - Non-Migrating

PVC - Polyvinyl Chloride

VDP - Velocity of Propagation