

PRODUCT DATA SHEET

7861 Airport Highway, Pennsauken, NJ 08109 • (800)346-4378 • Sales@seminolewire.com

60°C

300 V-AC

Part Number 2440 Description 18AWG Automotive Zip Cord

Application Amateur Radio, Automotive alarm and stereo, Robotics, R/C, and other general applications

Approvals/Ratings ---Compatibility ----

Construction & Specifications

Materials	Description	Specification/Standard
Conductor	Stranded Bare Copper	18AWG
Dielectric		
Stranding	19/31AWG	0.0092 in
Insulation	Polyvinyl Chloride (PVC)	0.025 in
Number of conductors	2	
Number of pairs		
Pair Lay Length		
Cable Lay Length		
Shield		
Drain		
Jacket Insulation		
Overall Cable Diameter		0 100 in v 0 215 in

Overall Cable Diameter ---- 0.100 in x 0.215 in

Cross-section diagram (not to scale)



Electrical & Environmental Properties









Temperature Rating Sunlight Resistant Voltage Rating Operating Voltage

Capacitance Between Conductors @ 1 KHz
Capacitance Between Conductor(s) to Shield @ 1KHz
DC Resistance per Conductor @ 20°C

DC Resistance per Conductor @ 20° C 5.46 ($\Omega/1000$ ft) Impedance ----(Ω) Velocity of Propagation ---- (%)

Attenuation ---- (db/1000ft)
Max. Pulling Tension 60 (lbs)

Flongation 50 (lbs)
Elongation 30 (%)
Tensile Strength @ 37,000 PSI 90 (lbs)
Min. Bend Radius/ Minor Axis ---- (in)

Miscellaneous Information

Insulation Color* Red / Black Pairing Combination* ----

Jacket Color* ---

Print* JSC WIRE & CABLE #2440 AUTOMOTIVE ZIP CORD 18 AWG ROHS PROUDLY MADE IN THE USA <SEQ FT>

Weight ~ 19.7 lbs. / 1000 ft.

Type* & Size* Packaging* & Pallets*

Put Up Length* 50 – 1000 Ft Plastic Spool Plain Corrugated Carton, Domestic Plywood Pallet

1000-5000ft Plywood Reel Plain Corrugated Wrap, Domestic Plywood Pallet

Warranties & Disclaimer

All product data presented is for informational purposes only and does not create a binding obligation or liability on Seminole and JSC Wire and Cable Co Inc or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to standard terms and conditions. Seminole and JSC Wire and Cable Co Inc disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Seminole and JSC Wire and Cable Co Inc. Any information contained herein shall not be disclosed to any party without written consent of Seminole and JSC Wire and Cable Co Inc.

All products sold are warranted by company only to customers for: (i) resale; or (ii) use in business, government or original equipment manufacturer. Company warrants products against defects in materials and workmanship under normal use for a period of six months after the date of purchase from company, unless otherwise stated. Provided that company accepts the product for return during the limited warranty period, company may, at its option: (i) repair; (ii) replace; or (iii) refund the amount paid by customer. Customer must return the product to the appropriate company branch as designated by company, shipping costs prepaid. Company's repair, replacement, or refund of amounts paid by customer for the product, shall be customer's sole and exclusive remedy.

^{*}Items can be customized. The customer accepts all factory lengths and +/- 10 percent of total order required.