



CABLE X-PERTS INC. IS A MANUFACTURER OF HIGH-QUALITY CABLE ASSEMBLIES.



We are proud to be a part of Seminole Wire & Cable family of brands which includes JSC brand coaxial cables. We achieve fastest in the industry order delivery by consolidating stock of cables and assembly materials. All raw materials are carefully sourced, and cable is manufactured in Pennsauken, NJ.

OUR PL-259 CONNECTOR IS SPECIFICALLY DESIGNED AND MADE FOR CABLE X-PERTS



RG-8X COAXIAL ASSEMBLY-15YR GUARANTEE

ATTENUATION		KEY FEATURES
MHz	db/100ft	HF applications 1-30 MHz
1	0.3	Maximum 875 Watts
10	0.9	Lightweight and portable
30	2	Direct Burial with waterproof shrink tubing
50	2.3	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.

RG-213 COAXIAL ASSEMBLY-15YR GUARANTEE

ATTENUATION		KEY FEATURES
MHz	db/100ft	MIL-C-17
10	0.55	Non-Migrating PVC Jacket
50	1.3	LOW LOSS HF COAX
100	1.9	Direct Burial with waterproof shrink tubing
200	2.7	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.

RG-8/U COAXIAL ASSEMBLY-15YR GUARANTEE

ATTENUATION		KEY FEATURES
MHz	db/100ft	LOW LOSS
10	0.47	Durable UV Resistant, PVC Jacket
50	1.2	1 – 50 MHz or 6 METERS
100	1.8	Direct Burial with waterproof shrink tubing
200	2.7	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.



400UF COAXIAL ASSEMBLY-15YR GUARANTEE (9913 Type)

ATTENUATION		KEY FEATURES
MHz	db/100ft	LMR-400-UF (BELDEN 9913) TYPE
30	0.8	Non-Migrating PVC Jacket
50	1.1	LOW LOSS UHF/VHF
150	1.8	Direct Burial with waterproof shrink tubing
450	3.3	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.

DBFLEX400 COAXIAL ASSEMBLY-20YR GUARANTEE

ATTENUATION		KEY FEATURES
MHz	db/100ft	FLEXIBLE LOW LOSS 400
30	0.8	UV and Weather Resistant PE Jacket
50	1.1	LOW LOSS UHF/VHF
150	1.8	Direct Burial with waterproof shrink tubing
450	3.3	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.

LMR400 TYPE COAXIAL ASSEMBLY-20YR GUARANTEE

ATTENUATION		KEY FEATURES
MHz	db/100ft	LMR-400 TYPE, SOLID CONDUCTOR
30	0.7	UV and Weather Resistant PE Jacket
50	0.9	LOW LOSS UHF/VHF
150	1.5	Direct Burial with waterproof shrink tubing
450	2.7	Standard lengths (ft): 1.5, 3, 6, 9, 12, 18, 25, 50, 75, 100, 150.



SALES AND CUSTOM ASSEMBLIES

1(800)828-3340

WWW.CABLEXPERTS.COM

Look for 'Cable Experts' on Amazon



BULK COAXIAL CABLES

PART No.	TYPE	KEY FEATURES
3750	RG-174	26AWG CCS, TINNED COPPER BRAID
3150	RG-58/U	20AWG SOLID COPPER, COPPER BRAID
3110	RG-58A/U	20AWG STRANDED, COPPER BRAID
3780	RG-213	STRANDED COPPER, COPPER BRAID, NON-MIGRATING
3030	RG-8/U	STANDED COPPER, COPPER BRAID
3061	RG-8X	16AWG STRANDED, COPPER BRAID, NON-MIGRATING
3062	DBF240F	FLEXIBLE 240 TYPE, ALUMINUM SHIELD, TIN BRAID, PE JACKET
3063	LL240F	FLEXIBLE 240 TYPE, ALUMINUM SHIELD, TIN BRAID, NON-MIGRATING
3830	LL240	LMR240 TYPE, ALUMINUM SHIELD, TIN BRAID, PE JACKET
3810	LL400	LMR400 TYPE, ALUMINUM SHIELD, TIN BRAID, PE JACKET
3815	9913 TYPE	LMR400 TYPE, ALUMINUM SHIELD, TIN BRAID, NON-MIGRATING
3825	DBF400	FLEXIBLE LMR400 TYPE, ALUMINUM SHIELD, TIN BRAID, PE JACKET

ROTOR CABLES

PART No.	TYPE	KEY FEATURES
5932	20/3	20AWG 3 CONDUCTOR, PVC
5942	20/4	20AWG 4 CONDUCTOR, PVC
5971	18/2 + 22/6	18/2 + 22/6, 8 CONDUCTOR, PVC
5973	16/2 + 18/6	16/2 + 18/6, 8 CONDUCTOR, HEAVY DUTY, PE JACKET
5976	18/6	18AWG 6 CONDUCTOR, YAESU ROTOR APPLICATION

LADDER LINE

PART No.	TYPE	KEY FEATURES
1320	300 OHM	20AWG STRANDED COPPER, PE INSULATED
1321	300 OHM	18AWG STRANDED CCS, PE INSULATED
1315	450 OHM	16AWG STRANDED CCS, PE INSULATED
1317	450 OHM	18AWG STRANDED CCS, PE INSULATED
1318	450 OHM	18AWG SOLID CCS, PE INSULATED